

Street Fighter RGB™

The powerful Street Fighter™ now available with the flexibility of color-changing RGB.



SPECIFICATIONS

Beam Angle	160° Low Dome, Batwing Optic	
Certifications	UL & cUL Recognized (SAM Manual), CE, RoHs	
Dimensions	0.7"W x 3.63"L x 0.35"H	
Efficacy	RED	33 LM/W
	GREEN	71 LM/W
	BLUE	19 LM/W
	ALL	38 LM/W
Fastening	Peel & stick / Mechanical screw hole	
Input	12VDC	
Intensity	RED	7 LM/mod (12.6 LM/ft.)
	GREEN	15 LM/mod (27 LM/ft.)
	BLUE	4 LM/mod (7.2 LM/ft.)
	ALL	25 LM/mod (45 LM/ft.)
Max Mods (Series)	45 mods (25 ft.)	
Operating Temp	-40° to +60°C	
Packaging	90 mods (50 ft.) per bag or 1,080 mods (600 ft.) per case	
Power	COLORS	0.21W/mod (0.378W/ft.)
	ALL	0.65W/mod (1.17W/ft.)
Power Supply	P-LED 12VDC	
Protection Grade	IP67	
Run Footage	90 mods (50 ft.)/60W PS	
Spacing	1.8 mods/ft. (fully stretched)	
Warranty	10-Year Product / 5-Year Limited Labor	

PRODUCT OPTIONS

Product	Wavelength	UL Part Number	Ordering Part Number
All	N/A	PL-OP2-SC3-P-RGB	M-SFCX3-3C
Red	625nm	PL-OP2-SC3-P-RGB	M-SFCX3-3C
Green	525nm	PL-OP2-SC3-P-RGB	M-SFCX3-3C
Blue	460nm	PL-OP2-SC3-P-RGB	M-SFCX3-3C

FEATURES

- For use in channel letters
- Cycle through a variety of colors or keep a unique color stationary with RGB
- Wide module spacing reduces module count and installation time
- Great in areas with indirect water exposure or salt spray

WIRING DETAILS

Gray	Positive
Red	Negative
Green	Negative
Blue	Negative

RECOMMENDED COVERAGE CHART

Depth	Max. Stroke	Row Spacing
	Single Row	Multi-Rows O.C.
4"	9"	6"
5"	12"	10"
6"	14"	12"

Note: Product and depth may vary depending on face material and desired brightness.

